

STANLEY®



HP210 POWER UNIT

The STANLEY® Hydraulic Power Unit HP210 is specifically engineered for safety and optimal performance. It features a hydraulic circuit flow with a tool circuit lockout during start-up, allowing for secure operation. Additionally, the engine speed can be manually controlled to provide either 8 or 12 GPM hydraulic flow. The unit is equipped with a convenient lift handle, making picking it up easy to move around. With its compact design, this hydraulic power unit is perfect for fulfilling all your on-site hydraulic power requirements, especially when operating STANLEY'S line of hydraulic handheld tools.

HP210 POWER UNIT

FEATURES

- Compact and lightweight
- Easy lift and release handle
- Quartz Hour Meter
- In-Tank hydraulic filtration
- Pressurized engine oil lubrication

SPECIFICATIONS

OUTPUT CAPACITY	TWO 4 GPM OR ONE 8 GPM / TWO 15 LPM OR ONE 30 LPM
PRESSURE	2000 PSI / 140 BAR
HYDRAULIC RESERVOIR CAPACITY	3 GAL / 11 L
COUPLERS	HTMA FLUSH FACE
FUEL TANK CAPACITY	5.5 GAL / 20.8 L
ENGINE	BRIGGS & STRATTON 18 HP
WEIGHT	334 LBS / 151.5 KG
LENGTH	36 IN. / 915 MM
WIDTH	23 IN. / 585 MM
HEIGHT	29.5 IN. / 762 MM

ORDER INFORMATION

PART NO.	DESCRIPTION
HP210B	INCLUDES WHEELS AND LIFT HANDLES
HP210BK	INCLUDES SKID MOUNT

ACCESSORIES

PART NO.	DESCRIPTION
31848	DUAL HOSE, 50 FT X 1/2 IN. WITH COUPLERS
31972	DUAL HOSE, 25 FT X 1/2 IN. WITH COUPLERS
58633	TWINNED HOSE, 25 FT X 1/2 IN. WITH COUPLERS
58634	TWINNED HOSE, 50 FT X 1/2 IN. WITH COUPLERS

STANLEY[®]

3810 SE Naef Road // Milwaukie, OR 97267 // 833-723-1843 // www.IndustrialToolsAndAttachments.com