



LABOUNTY®

www.LaBountyAttachments.com



**PRIMARY
&
SECONDARY
DEMO**

MRX SERIES

MULTI-JAW DEMOLITION TOOL

SINGLE-CYLINDER VERSATILITY

The MRX takes versatility to the next level with its three interchangeable jaws - a concrete pulverizer, concrete cracker, and shear - making it the ideal solution for primary and secondary demolition needs. Additionally, the MRX boasts a short center of gravity and 360-degree rotation, providing optimal maneuverability.

MULTI-JAW DEMOLITION TOOL

- **Jaw Interchange Visibility** for easier swapping
- **Improved Handling and Wear-Protection** on jaws
- **Reverse Cylinder** with internal hydraulic lines protects components from debris
- **Dual Rotation Motors** for superior control and reliability
- **Easy to Change Teeth** to minimize downtime
- **Cutting Blade** to remove nuisance rebar

CHOOSING THE RIGHT JAW - 5 MINUTE JAW CHANGES

CONCRETE PULVERIZER - CP



CONCRETE CRACKER - CC



SHEAR JAW - SH



SPECIFICATIONS

Model	Jaw	Weight (with jaw)*		Jaw Opening		Jaw Depth		Reach**		Min Excavator Weight - 3rd Member***	
		lbs	kg	in	mm	in	mm	ft	m	lbs	mTons
MRX 70	Shear (SH)	1,670	760	10	250	13	330	5.2	1.6	15,000	7
	Concrete Pulverizer (CP)	1,760	800	21	530	20	510	5.6	1.7	15,000	7
	Concrete Cracking (CC)	1,760	800	21	530	19	490	5.7	1.7	15,000	7
MRX 100	Shear (SH)	2,350	1,070	13	320	15	390	6.1	1.9	20,000	9
	Concrete Pulverizer (CP)	2,460	1,120	26	660	24	610	6.6	2.0	20,000	9
	Concrete Cracking (CC)	2,520	1,140	24	600	24	610	6.7	2.0	20,000	9
MRX 130	Shear (SH)	3,330	1,510	16	400	18	450	6.6	2.0	29,000	13
	Concrete Pulverizer (CP)	3,450	1,570	28	720	25	630	7.1	2.2	29,000	13
	Concrete Cracking (CC)	3,320	1,510	29	740	28	710	7.3	2.2	29,000	13
MRX 180	Shear (SH)	4,520	2,050	17	430	18	470	7.5	2.3	40,000	18
	Concrete Pulverizer (CP)	4,740	2,150	28	720	26	660	7.9	2.4	40,000	18
	Concrete Cracking (CC)	4,620	2,100	29	750	27	690	8.3	2.5	40,000	18
MRX 220	Shear (SH)	6,070	2,800	19	480	20	510	8.3	2.5	48,000	22
	Concrete Pulverizer (CP)	6,270	2,800	33	830	30	760	8.8	2.7	48,000	22
	Concrete Cracking (CC)	6,180	2,800	33	840	31	790	9.1	2.8	48,000	22
MRX 260	Shear (SH)	8,220	3,700	20	500	22	570	8.9	2.7	57,000	26
	Concrete Pulverizer (CP)	8,600	3,900	33	840	32	800	9.4	2.9	57,000	26
	Concrete Cracking (CC)	8,290	3,800	33	820	32	810	9.4	2.9	57,000	26
MRX 360	Shear (SH)	9,270	4,200	21	540	22	570	8.8	2.7	79,000	36
	Concrete Pulverizer (CP)	10,100	4,600	37	950	36	920	9.5	2.9	79,000	36
	Concrete Cracking (CC)	9,630	4,400	36	900	36	900	9.7	3.0	79,000	36
MRX 500	Shear (SH)	13,600	6,170	23	570	26	660	9.8	3.0	117,000	53
	Concrete Pulverizer (CP)	15,030	6,820	43	1,100	41	1,030	10.8	3.3	117,000	53
	Concrete Cracking (CC)	14,610	6,630	45	1,150	42	1,070	11.0	3.4	117,000	53
MRX 750	Shear (SH)	19,820	9,000	28	700	30	760	11.1	3.4	165,000	75
	Concrete Pulverizer (CP)	21,320	9,680	46	1,180	43	1,100	11.8	3.6	165,000	75
	Concrete Cracking (CC)	20,670	9,380	46	1,180	46	1,160	11.8	3.6	165,500	75

*Weight includes standard excavator mounting bracket. Attachment weight may vary depending on mounting configuration as well as options.

** Reach is measured from the attachment mounting pivot (boom or stick) forward to the end of the jaw.

*** Excavator weight range is a guide only. 2nd member configurations at or near min/max excavator weight and all 3rd member configurations must be preapproved by LaBounty. Quick couplers, short swing machines, long arms all impact carrier size recommendation.

LaBounty reserves the right to improve, update, or change the product specifications, appearance, or functional attributes without notice.