



**LABOUNTY®**



# MSD LEGEND

## MOBILE SCRAP SHEARS

### **A NEW LEGEND - FORGED IN INNOVATION**

The objective was simple: reduce maintenance and boost productivity. As a result, productivity and uptime were optimized. LaBounty® shears have demonstrated their effectiveness in scrap metal processing, bridge deconstruction, and industrial demolition for many years. We are thrilled to unveil the Legend Series Mobile shear, which includes the industry's exclusive fully protected and indexable mobile shear tip - the Dual Max™ piercing tip.

# MSD LEGEND SERIES MOBILE SCRAP SHEARS



## SPECIFICATIONS

Model	Weight*		Jaw Opening		Jaw Depth		Reach**		Min Excavator Weight - 2nd Member***		Min Excavator Weight - 3rd Member***	
	lbs	kg	in	mm	in	mm	ft	m	lbs	mTons	lbs	mTons
MSD 1500	7,000	3,200	21	540	25	640	6.8	2.1	26,000	12	55,000	25
MSD 1500R	7,440	3,400	21	540	25	640	10.0	3.1	40,000	18	66,000	30
MSD 2000	9,000	4,100	28	710	29	740	8.0	2.4	42,000	19	70,000	32
MSD 2000R	11,000	5,000	28	710	29	740	10.8	3.3	48,000	22	88,000	40
MSD 2250	10,600	4,800	30	760	30	760	8.6	2.6	44,000	20	88,000	40
MSD 2250R	12,700	5,800	30	760	30	760	11.7	3.6	53,000	24	99,000	45
MSD 2500	11,900	5,400	31	790	33	840	8.7	2.7	51,000	23	88,000	40
MSD 2500R	14,800	6,700	31	790	33	840	12.7	3.9	66,000	30	110,000	50
MSD 3000	14,200	6,400	34	860	37	940	10.0	3.1	66,000	30	143,000	65
MSD 3000R	17,100	7,800	34	860	37	940	13.1	4.0	88,000	40	154,000	70
MSD 4000	17,100	7,800	38	970	43	1090	11.5	3.5	77,000	35	143,000	65
MSD 4000R	19,800	9,000	38	970	43	1090	14.8	4.5	99,000	45	176,000	80
MSD 4500	18,700	8,500	39	990	43	1090	11.0	3.4	88,000	40	165,000	75
MSD 4500R	21,300	9,700	39	990	43	1090	14.3	4.3	110,000	50	187,000	85

\*Weight includes standard excavator mounting bracket. Attachment weight may vary depending on mounting configuration as well as options.

\*\* Reach is measured from the attachment mounting pivot (boom or stick) forward to the end of the jaw.

\*\*\* Excavator weight range is a guide only. 2nd member configurations at or near min/max excavator weight and all 3rd member configurations must be preapproved by LaBounty. Quick couplers, short swing machines, long arms all impact carrier size recommendation.

LaBounty reserves the right to improve, update, or change the product specifications, appearance, or functional attributes without notice.

# LABOUNTY

1538 Hwy 2 // Two Harbors, MN 55616 // 833-723-1843 // [www.stanleyinfrastructure.com](http://www.stanleyinfrastructure.com)

2024.03.28