

STANLEY®



TA54 HYDRAULIC TAMPER

The TA54 Tamper - a remarkably efficient tool designed for compacting soil around utility poles, signs, and fence posts. With its closed hydraulic system and minimal moving parts, maintenance requirements are low and its lifespan is long. Delivering 1,600 blows per minute with a 2-1/2 inch stroke, it ensures optimal compaction while remaining easily repositionable. This tamper creates a solid and stable foundation by reducing air pockets and increasing soil density, effectively preventing shifting or leaning over time and providing essential stability and support for structures.

TA54 HYDRAULIC TAMPER

FEATURES

- The long stroke keeps the TA54 above the fill making it easy to reposition the tool
- Only 2 moving parts
- Depending on model the TA54 is furnished with a 3 x 8 inch kidney foot, a 4 or 6 inch diameter round shoe or a 4 x 8 inch rectangular shoe can be ordered as options to the base model

SPECIFICATIONS

PERFORMANCE	1600 BLOWS PER MINUTE
FLOW RANGE	3 - 9 GPM / 11 - 34 LPM
PRESSURE	1000 - 2000 PSI / 70 - 140 BAR
WEIGHT (TA54103,TA54603, AND TA54113)	30 LBS / 14 KG
WEIGHT (TA54603A)	37 LBS / 17 KG
LENGTH W/O HOSES AND HOSE WHIPS (TA54103 AND TA54113)	71 IN. / 180 CM
LENGTH W/O HOSES AND HOSE WHIPS (TA54603 AND TA54603A)	69 IN. / 175 CM
WIDTH	4 IN. / 10 CM
HANDLE LENGTH	36 IN. / 91 CM
CONNECTION	ADAPTERS OR HOSES & COUPLERS
HOSES	ONLY WITH MODEL T54603A
COUPLERS	1/2 IN. SAE O-RING PORT
SYSTEM TYPE	HTMA TYPE I AND TYPE II

ORDER INFORMATION

PART NO.	DESCRIPTION
TA54103	TAMPER - OC, KIDNEY SHOE, 71 IN. LONG, VALVE IN HANDLE, COUPLERS, NO HOSE WHIPS
TA54603	TAMPER - OC, KIDNEY SHOE, 69 IN. LONG, NO VALVE IN HANDLE, COUPLERS, NO HOSE WHIPS
TA54603A	TAMPER - OC/CC, KIDNEY SHOE, 69 IN. LONG, IN-LINE VALVE, HOSE WHIPS AND COUPLERS
TA54113	TAMPER - ROUND SHOE, 71 IN. LONG, VALVE IN HANDLE, COUPLERS, NO HOSE WHIPS

ACCESSORIES

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
00833	KIDNEY SHOE	72264	IN-LINE VALVE ASSEMBLY OC/CC
00840	ROUND SHOE, 6 IN. DIAMETER	021120	TAMPER SLEEVE TOOL
01070	RECTANGULAR SHOE	01949	SLEEVE INSTALLATION WRENCH
35784	8 FT. HOSE (2 REQUIRED)	04337	O-RING TOOL KIT