

# STANLEY®

www.stanleyinfrastructure.com



## CS25 / CS28

### POLE CHAIN SAWS

#### LIGHTWEIGHT // CONVENIENT

The CS25 and CS28 pole chain saws are ideal for use by right-of-way crews, utilities, parks departments and grounds-keepers. Lightweight, they feature fiberglass poles for convenient handling in tight spots and automatic chain oiling for long, reliable service.

The CS28 is designed for HTMA Type II circuits and has an optimum flow of 8 gpm / 30 lpm. The CS25 is ideal for HTMA Type I circuits commonly found on bucket trucks where hydraulic circuit flow is often limited to 4-6 gpm / 15-23 lpm.

For greater versatility, the Stanley "Dual Spool" permits the user to adjust the saw to operate from either open or closed-center circuits.

The CS25/CS28 use a low kickback, .325-pitch saw chain for added safety. The flow rating is easily changed by replacing the gear chamber and two gears.

# CS25 / CS28 POLE CHAIN SAWS

## FEATURES AND BENEFITS

- Pole centerline close to bar centerline reducing operator fatigue
- External bar oiler makes for quick and convenient adjustments
- Easy to source replacement parts
- OC/CC dual spool - match the tool hydraulics to the circuit
- Extra long bucking face/brush management
- Rim sprocket provides smoother operation, retains chain
- Guide plates keeps loose chain in place
- Improved handle ergonomics while wearing gloves
- One-piece oil tube and pole assembly for increased durability
- Increased connection strength by 15% to provide robust durability

## SPECIFICATIONS

	PCS25	PCS28
Cut Capacity	13 in / 33 cm	13 in / 33 cm
Weight*	10.4 & 10.9 lb / 4.7 & 5 kg	10.4 & 10.9 lb / 4.7 & 5 kg
Overall Length**	78 & 91 in / 198 & 231 cm	78 & 91 in / 198 & 231 cm
Pressure	1000-2000 psi / 70-140 bar	1000-2000 psi / 70-140 bar
Flow Range	4-6 gpm / 15-23 lpm	7-9 gpm / 26-34 lpm
Optimum Flow	5 gpm / 20 lpm	8 gpm / 30 lpm
Porting	-8 SAE	-8 SAE
Connect Size / Type	3/8 NPT Male Adapter	3/8 NPT Male Adapter

\* Weight includes bar and chain but not quick couplers.

\*\* Length includes bar and chain but not quick couplers.

## ORDER INFORMATION

MODEL NO.	DESCRIPTION
CS25811	Long Reach 91"/231 cm, oc/cc, 4-6 gpm/15-23 lpm
CS25812	Short Reach 78"/198 cm, oc/cc, 4-6 gpm/15-23 lpm
CS28811	Long Reach 91"/231 cm, oc/cc, 7-9 gpm/26-34 lpm
CS28812	Short Reach 78"/198 cm, oc/cc, 7-9 gpm/26-34 lpm
CS25811L11	Long Reach 91"/231 cm, oc/cc, 4-6 gpm/15-23 lpm Portuguese Label
CS25812L11	Short Reach 78"/198 cm, oc/cc, 4-6 gpm/15-23 lpm Portuguese Label

## ACCESSORIES

PART NO.	DESCRIPTION
88685	Coupler Set (Male & Female)
56725	Hose Whip, 18 in.
05144	Chain / Bar Guard
07616	Sprocket Spline Adapter
07629	Rim Sprocket 0.325 P
08347	13 in (33 cm) saw bar
08348	Saw Chain for 13 in (33 cm) bar
11464	Scrench
11294	Flat File
11298	Depth Gauge
12363	File guide with file

## WARRANTY

Stanley tools and associated parts are warranted against defects in materials and workmanship for a period of 18 months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum voltage and current ratings are exceeded.