

BR87 HYDRAULIC BREAKER

STANLEY®



SPECIFICATIONS

ITEM		
Output	1080 Blows Per Minute	
Capacity	1-1/8 x 6 in. Hex 1-1/4 x 6 in. Hex*	1-1/8 in. x 15.2 cm Hex 1-1/4 in. x 15.2 cm Hex*
Weight	84 lbs	38 kg
Length	29 in.	73.5 cm
Width (At Handles)	16 in.	41 cm
Pressure	1500 - 2000 psi	105 - 140 bar
Flow Range	7 - 9 gpm	26 - 34 lpm
Optimum Flow	8 gpm	30 lpm
Porting	8 SAE O-Ring	
Connector	3/8 in. Male Pipe Hose End	

*Underwater model not available with Easi-Ride™ foot.

Stanley's line of handheld breakers contains a wide selection of models suited to virtually any application.

The BR87 is a heavy duty tool for work in the 90 pound class and above for 8+" concrete applications. It is highly productive in utility construction, street maintenance, repair of water and gas mains, and general contracting jobs.

A feathering on/off valve controls speed, making start up and initial tool placement easy.

A diaphragm accumulator provides trouble free operation and will handle system back pressures up to 250 psi (17 bar)

Operates on open center systems and is available in 1-1/8 or 1-1/4 inch chuck hex sizes.

Complete line of steels for breaking, cutting or driving available from Stanley Hydraulic Tools.

Undewater models available. Refer to ordering information.



STANLEY®

Stanley Hydraulic Tools | 3810 SE Naef Road | Milwaukie, Oregon 97267 | +01.503.659.5660 | 800.972.2647 | www.stanleyhydraulic.com

BR87 HYDRAULIC BREAKER

Model Numbers	
Model	Description
BR87120	BR87 T-Handle Breaker, oc, 1-1/8 in. Hex
BR87120E	BR87 T-Handle, oc, 1-1/8 in. Hex, Easi-Ride™
BR87130	BR87 T-Handle Breaker, oc, 1-1/4 in. Hex
BR87130E	BR87 T-Handle Breaker, oc, 1-1/4 in. Hex, Easi-Ride™ Foot
BR87320	BR87 Underwater T-Handle Breaker, oc, 1-1/8 in. Hex

Note: All models listed above ship with hose whips.

Service Tools	
Part No.	Description
04596	Seal Kit
04908	Split Ring (Auto Valve Removal)
04909	Spacer (Flow Sleeve Install)
04910	Flow Sleeve Removal Tube
05508	Accumulator Disassembly Tool
05640	Accumulator Cylinder Puller
Test Equipment	
02835	Accumulator Tester
04182	Flow and Pressure Tester
06545	Accumulator Charge Kit

Part	Description
1-1/8 in Hex X 6 in. Shank	
02332	Asphalt Cutter, 5 in. / 12.7 cm Blade x 11 in. / 28 cm*
02333	Moil Point, 14 in. / 25.6 cm*
02334	Chisel, 3 in. / 76 mm Blade x 14 in. / 35.6 cm*
03990	Chisel Point, 14 in. / 35.6 cm*
04176	Ground Rod Driver, 1 in. / 25 mm Rod
08106	Asphalt Wedge, 12 in. / 30.5 cm*

*Length measured from bottom tip of tool to bottom

Part	Description
1-1/4 in Hex X 6 in. Shank	
09262	Clay Spade, 5-1/2 in. / 133 mm Blade
02335	Asphalt Cutter, 5 In. / 12.7 Cm Blade x11 In. / 28 cm*
02336	Moil Point, 14 in. / 35.6 cm*
02337	Chisel, 3 in. / 76 mm Blade x 14 in. / 35.6 cm*
03990	Chisel Point, HD, 1 in. / 25 mm Wide Blade x 14 in. / 35.6 cm*
04367	Ground Rod Driver, 1 in. / 25 mm Rod
04404	Heavy Duty Moil Point, 18 in. / 45.7 cm*
04405	Clay Spade, 8 in. / 20.3 cm Blade
09262	Clay Spade, 5-1/2 in. / 14 cm

*Length measured from bottom tip of tool to bottom

All stanley hydraulic tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult stanley hydraulic tools.

WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.