

# STANLEY®



## GR29 UNDERWATER GRINDER

The STANLEY® Hydraulic GR29 Grinder is a right angle grinder ("vertical grinder") that can be used for grinding and cleaning in underwater applications with a variety of wheels, brushes and attachments. The high torque gear motor drives a standard 5/8 - 11 threaded spindle. A 9" adjustable wheel guard, two position assist handle and trigger guard are standard. Painted hi-visibility yellow.

# GR29 UNDERWATER GRINDER

## FEATURES

- Integral Stanley Hyrevz gear motor produces high torque
- Stainless Steel spool and fasteners
- Two position assist handle for right/left hand operation
- Oversized trigger with guard for diver comfort
- Adjustable wheel guard for infinite positions
- Plastisol covered handle for comfortable ergonomic grip
- Use with grinding wheels, hull scrubbing brushes, wire and nylon brushes, barnacle busters and Desmond wheels
- 3200 rpm @ 12 gpm
- Cast-in lifting eye

## SPECIFICATIONS

CAPACITY	9 IN. / 23 CM WHEEL
SPINDLE	5/8 IN. - 11 THREADED
CIRCUIT TYPE	OPEN CENTER
FLOW RANGE	4-12 GPM / 15-45 LPM
WORKING PRESSURE	1000-2000 PSI / 70-140 BAR
FULL RELIEF SETTING	2250 PSI / 155 BAR
RPM	3200 @ 12 GPM / 45 LPM
WEIGHT (WITH GUARD)	15 LBS / 6.8 KG
LENGTH	11 IN. / 28 CM
WIDTH (WITH GUARD)	10¼ IN. / 26 CM
HYDRAULIC PORTS	-8 SAE O-RING
CONNECTION SIZE AND TYPE	3/8 IN. MALE PIPE ADAPTER
COUPLERS	VARIES WITH MODEL(SEE ORDERING INFORMATION)
HOSE WHIPS	NO (SEE ACCESSORIES)

## ORDER INFORMATION

PART NO.	DESCRIPTION
GR29310	GRINDER, UNDERWATER, LESS COUPLERS
GR2930101	GRINDER, UNDERWATER, COUPLERS, CE

## ACCESSORIES

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
03971	FLUSH-FACE COUPLING SET, 3/8 IN. NPT	31848	DUAL HOSE, 50 FT. X 1/2 IN., WITH COUPLERS
03974	FLUSH-FACE COUPLING SET, 1/2 IN. NPT	31972	DUAL HOSE, 25 FT. X 1/2 IN., WITH COUPLERS
06830	HOSE WHIP 18 IN. LONG, -8 SAE X 1/2 IN. NPT	58633	TWINNED HOSE, 25 FT. X 1/2 IN., WITH COUPLERS
02587	GRINDING WHEEL FOR METAL, 9 IN. DIAMETER X 5/8 - 11 THD	58634	TWINNED HOSE, 50 FT. X 1/2 IN., WITH COUPLERS
02588	GRINDING WHEEL FOR MASONRY, 9 IN. DIAMETER X 5/8 - 11 THD		
03691	GRINDING WHEEL, 7 IN. DIAMETER X 5/8 - 11 THREAD		
05194	ADAPTER, 5/8 - 11 THREAD, DEPRESSED CENTER WHEEL		

When hydraulic hose exceeds 100' (30.4 m) in length, increase I.D. of both pressure and return hose. For more information, consult STANLEY Hydraulic Tools.

# STANLEY®

3810 SE Naef Road // Milwaukie, OR 97267 // 833-723-1843 // [www.IndustrialToolsAndAttachments.com](http://www.IndustrialToolsAndAttachments.com)