

STANLEY[®]

Hydraulic Tools

**HYDRAULIC
HANDHELD
BREAKERS**



NOW AVAILABLE IN THREE PERFORMANCE CLASSES

- **MORE POWER**

Stanley Hydraulic breakers feature a concrete removal rate that's *20% greater per minute than the same class conventional pneumatic breakers.

- **LOW VIBRATION ZONE**

Zone A ISO 5349 Rating allows a user to run 4-8 consecutive hours. A comparable pneumatic which is rated Zone C can only run between .5 hr -2 hours.

- **PATENTED EZ RIDE FOOT**

Offers precision control when starting to break.

- **PROPRIETARY DOUBLE SEAL**

Increases efficiency and reduces downtime by preventing job site contamination.

- **LESS NOISE**

*4X quieter than the pneumatic alternative.

- **WATER-RESISTANT**

Can be used in wet or underwater conditions – unlike electric breakers.

- **BIT LOCK SYSTEM**

Helps keep parts from loosening or coming apart during operation.

- **NEW LEG GUARD**

Design provides greater control and comfort.

- **COLD WEATHER OPERATION**

Hydraulics will not freeze up in cold conditions – unlike pneumatic alternatives.

- **NO EXHAUST**

Hydraulic Breakers are exhaust free – unlike pneumatic breakers.

** Data provided from a 3rd party research firm.*



CONQUER THE ROAD



PERFORMANCE CODING

CHOOSE THE RIGHT BREAKER FOR THE RIGHT OPERATION



40/50 LB CLASS BREAKERS

- Designed for 2-6" Concrete operations.



70 LB CLASS BREAKERS

- Designed for 6-8" Concrete operations.



90 LB CLASS BREAKERS

- Designed for 8+" Concrete operations.

ADVANTAGES

- Hydraulic breakers CAN BE USED IN WET CONDITIONS (Unlike competitive electric breakers)
- Hydraulic breakers RUN QUIETER AND SMOOTHER than pneumatic breakers
- Hydraulic breakers and hoses WON'T FREEZE UP in sub-freezing conditions (Unlike competitive pneumatic breakers)
- ZERO TOOL EXHAUST for user health and safety-unlike gas (carbon monoxide exhaust) and air tools (dust/dirt exhaust)

STANDARD BREAKER MODELS

40/50 LB
2-6" CONCRETE

BREAKER CLASS	MODEL NUMBERS	SHANK SIZE	HEX LENGTH	HANDLE CONFIGURATION	FOOT	GPM
BR45						
40/50 CLASS	BR45120	1-1/8"	6"	T	Standard	8 gpm
40/50 CLASS	BR45130	1-1/4"	6"	T	Standard	8 gpm
40/50 CLASS	BR45120E	1-1/8"	6"	T	EZ Ride	8 gpm
40/50 CLASS	BR45130E	1-1/4"	6"	T	EZ Ride	8 gpm
40/50 CLASS	BR45150	1"	4-1/4"	T	Standard	8 gpm
40/50 CLASS	BR45550	1"	4-1/4"	T	Standard	5 gpm
40/50 CLASS	BR45125S	1-1/8"	6"	Anti-Vib	EZ Ride	8 gpm
40/50 CLASS	BR45110	7/8"	3-1/4"	T	Standard	8 gpm
40/50 CLASS	BR45135S	1-1/4"	6"	Anti-Vib	Standard	8 gpm

70 LB
6-8" CONCRETE

BR67						
70 CLASS	BR67120	1-1/8"	6"	T	Standard	8 gpm
70 CLASS	BR67130	1-1/4"	6"	T	Standard	8 gpm
70 CLASS	BR67130E	1-1/4"	6"	T	EZ Ride	8 gpm
70 CLASS	BR67120E	1-1/8"	6"	T	EZ Ride	8 gpm
70 CLASS	BR67125	1-1/8"	6"	Anti-Vib	Standard	8 gpm
70 CLASS	BR67135	1-1/4"	6"	Anti-Vib	Standard	8 gpm

90 LB
8+" CONCRETE

BR87						
90 CLASS	BR87120	1-1/4"	6"	T	Standard	8 gpm
90 CLASS	BR87130	1-1/4"	6"	T	Standard	8 gpm
90 CLASS	BR87130E	1-1/8"	6"	T	EZ Ride	8 gpm
90 CLASS	BR87120E	1-1/8"	6"	T	EZ Ride	8 gpm

CONTACT STANLEY
HYDRAULIC TOOLS

STANLEY[®]

Hydraulic Tools

N.A. Version

Stanley Hydraulic Tools Division of Stanley Black & Decker

3810 S.E. Naef Road Milwaukie, OR 97267-5698 U.S.A.

Tele: (503) 659-5660 Fax: (503) 652-1780

www.stanleyhydraulic.com