

# RV06 / IP16



# ROCKER VALVE / INTENSIFIER



RV06



IP16

With its own built-in oil reservoir for the high pressure output, the **IP16** can handle circuits with extreme back-pressure in the oil return lines. As an added bonus, tools won't receive contamination from the truck circuit. Also, the oil in the **IP16** will maintain its dielectric qualities far longer.

The built-in reservoir also allows the **IP16** to handle very high oil temperatures and is not sensitive to the viscosity of the oil from the truck circuit.

The unloader valve in the **IP16** sounds an audible "click" when the preset pressure has been achieved assuring accurate die loads, crimp after crimp.

Connection can be made using quick couplers or hose. Since the porting is standard, you'll have no problem adapting the crimper or cutter you prefer. The versatility of the **RV06** connection allows you to use our full line of crimpers and cutters. In addition, you can use tools you already own, whether single or double acting.

The **IP16 Intensifier** provides up to 10,000 psi/690 bar of adjustable hydraulic power. It is used equally well with single or double-acting tools.

The **IP16** Intensifier can be driven from almost any HTMA Type I, II, or III hydraulic circuit either open or closed-center.

## OPERATION AND PERFORMANCE

ITEM	U.S.A.	METRIC
<b>RV06</b>		
Capacity	Rocker (auto return)	
Weight	2.6 lbs	1.18 kg
Length	5-1/8 in	13.2cm
Width	2 in	51 cm
Pressure	10,000 psi	690 bar
Porting	1/4 in female NPT	
<b>IP16</b>		
Reservoir Capacity	2 qt	1.9 ltr
Weight	12 lb (dry)	5.4 kg (dry)
Length	10.50 in	25.9 cm
Width	6 in	15.2 cm
Height	5 in	12.9 cm
Output Pressure	10,000 psi Up	690 bar
Hydraulic Pressure	to 2,500 psi	Up to 172.4 bar
Flow Range	3-10 gpm	11-38 lpm
Optimum Flow Porting	8 gpm	30 lpm
Connect Size and Type	-8 SAE O-ring 3/8 in NPT Male Pipe Adapter	

The Stanley **RV06 Rocker Valve** makes the use of single or double acting crimping and cutting tools more convenient than ever. Simply press the forward end of the rocker to advance the tool piston or depress the rear section of the rocker to retract the tool piston.

**RV06** is spring loaded to the "neutral" or "hold" position so when the rocker is released, the piston will remain in the position you desire. The smooth, precise action of the rocker allows the operator to maintain full control while "feathering" the rocker in both advance and retract mode.

The **RV06** features standard 1/4-inch female NPT ports for tool hook-up.

# RV06 / IP16

The Stanley logo is displayed in a bold, yellow, sans-serif font. The word "STANLEY" is contained within a black rectangular box. A registered trademark symbol (®) is located to the right of the box.

# ROCKER VALVE / INTENSIFIER

## ORDERING INFORMATION

ORDER NO.	DESCRIPTION
-----------	-------------

RV06000	RV06 Rocker Valve with 6 ft. Hoses and one High Pressure Quick Coupler Set. Open Center
IP16615D	IP16 Pressure Intensifier with Oil Sight Glass and high-pressure coupler set. Does not include flush face couplers

All Stanley hydraulic tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult Stanley hydraulic tools.

**WARRANTY:**

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.