



SPECIFICATIONS

ITEM	U.S.A.	METRIC
CAPACITY (SK58130)	7/8 in. Hex x 4-1/4 in. Shank	
CAPACITY	1 in. Hex x 4-1/4 in. Shank	
PERFORMANCE	3 in. x 20 ft. Deep Hole	
FLOW RANGE	7 - 9 gpm	26 - 34 lpm
PRESSURE	1500 - 2000 psi	105 - 140 bar
PORTS*	-8 SAE O-Ring (H), 1/2 in. NPT (A)	
WEIGHT	67 lbs	30 kg
LENGTH	26 in.	66 cm
WIDTH	18 in.	46 cm
CONNECTION	3/8 in. Male NPT Hose End	
HOSE WHIPS	Yes	
MOTOR	Integral	
* (H) = Hydraulic (A) = Air		

Features and Benefits

The Stanley SK58 Sinker Drill is designed for heavy-duty utility construction, blast hole drilling, leak detection for gas utilities, dowel drilling. A model is available for underwater use.

Models are available with air or water flushing to clear holes of debris.

The sinker drill features an easy start feathering trigger and a direct drive rotation motor for reliable service and fast and easy starting.

The rotation is independent of impact rate and is adjustable between 0 and 300 rpm. The sinker drill can drill up to a 3 in. (75 mm) diameter hole up to 20 ft (6 m) deep.

ORDERING INFORMATION

MODEL	PART NO.	DESCRIPTION
SK58	SK58110	Air, Flush Open Center System
SK58	SK58120	Water, Flush Open Center System
SK58	SK58130	Air, Flush Open Center System
SK58	SK58310	Underwater, Air, Flush Open Center System

ACCESSORIES

PART NO.	DESCRIPTION
CARBIDE ROCK BITS SHOULDER DESIGN FOR USE WITH AIR	
05177	1-3/8 in. Diameter, Hex Thread
05178	1-1/2 in. Diameter, Hex Thread
DRILL STEELS FOR USE WITH AIR	
04915	1 in. Hex x 4-1/4 in., Hex Thread 36 in. U/C
05168	1 in. Hex x 4-1/4 in., Hex Thread 12 in. U/C
05169	1 in. Hex x 4-1/4 in., Hex Thread 18 in. U/C
05170	1 in. Hex x 4-1/4 in., Hex Thread 24 in. U/C
05171	1 in. Hex x 4-1/4 in., Hex Thread 48 in. U/C
05172	7/8 in. Hex x 4-1/4 in., Hex Thread 12 in. U/C
05174	7/8 in. Hex x 4-1/4 in., Hex Thread 24 in. U/C
05175	7/8 in. Hex x 4-1/4 in., Hex Thread 36 in. U/C
05176	7/8 in. Hex x 4-1/4 in. Hex Thread 48 in. U/C
08905	1 in. x 4-1/4 in., Hex Thread 6 ft U/C
08906	1 in. x 4-1/4 in., Hex Thread 8 ft U/C
CARBIDE ROCK BITS FOR USE WITH WATER	
05189	2 in. Diameter, 125 Rope Thread
05190	2-1/4 in. Diameter, 125 Rope Thread
05191	2-1/2 in. Diameter, 125 Rope Thread
STRIKING BAR AND SECTIONAL DRILL STEEL FOR USE WITH WATER	
05183	1 in. Hex x 4 ft, 125 Rope Thread
05184	1 in. Hex x 5 ft, 125 Rope Thread
05192	Striking Bar, 1 in. Hex x 4-1/4 in., 125 Rope Thread, 5/16 Tube Size
05193	Coupling, 125 Rope Thread
06929	Replacement Cup Seal for Striking Bar

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

STANLEY[®]

Stanley Hydraulic Tools
3810 S.E. Naef Road
Milwaukie, Oregon 97267
Tel 503 • 659 • 5660
Fax 503 • 652 • 1780